



ZPMV2.E320803 Wiring, Printed - Component

For enhanced search functionality, please visit UL's [iQ™ Family of Databases](#).

Click on a product designation for complete information.

[Page Bottom](#)

Wiring, Printed - Component

[See General Information for Wiring, Printed - Component](#)

SURPASS PRINTED CIRCUIT BOARD CO LTD
669 HANGANG RD CHIGANG HUAQIAO
ECONOMIC DEVELOPMENT ZONE
HANJIANG DISTRICT
PUTIAN, FUJIAN 351117 CHINA

E320803

Type	Cond Width				Max			Max			
	Min	Cond	SS/	Area	Solder	Oper		Meets	C		
	Min	Edge	Thk	DS/	Diam	Limits	Temp	Flame	UL796	T	
	mm(in)	mm(in)	mic(mil)	DSO	mm(in)	C	sec	C	Class	DSR	I
Mass laminated (multilayered) printed wiring boards.											
L-4	0.10 (0.004)	0.20 (0.008)	17 (0.67)	DS	38 (1.5)	280	20	130	V-0	All	-
Multilayer printed wiring boards.											
L-M	0.10 (0.004)	0.16 (0.006)	17 (0.67) Int:34	DS	50.8 (2.0)	280	20	130	V-0	All	-
Single layer metal base printed wiring boards.											
LT-06	0.15 (0.006)	0.20 (0.008)	25 (0.98)	SS	50.8 (2.0)	288	20	125	V-0	All	*
Single layer printed wiring boards.											
L-2	0.10 (0.004)	0.20 (0.008)	17 (0.67)	DS	25.4 (1.0)	280	20	130	V-0	All	-
Single layer printed wiring boards, flammability only Recognition.											
L-2A	-	-	-	DS	-	280	20	-	V-0	-	-

* - CTI Rating is marked on individual board.

Marking: Company name or file number and type designation. May be followed by a suffix to denote factory identification or burning test classification.

Last Updated on 2015-07-15

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

